



- NOTE 1: FLOW MAY BE IN EITHER DIRECTION  
 NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.  
 NOTE 3: REFERENCE AWWA C-504-B & DRILLING (A.N.S.I. 250)  
 NOTE 4: NUMBER OF TURNS TO CLOSE = 103  
 NOTE 5: OPERATING BY 50mm AWWA OPERATING / WRENCH NUT  
 NOTE 6: "A" = (32) 2" DIAMETER BOLTS PER FLANGE  
 NOTE 7: "B" = (8) 2"-4.5 UNC x 2 1/4" DEEP TAPPED HOLES EACH FLANGE  
 NOTE 8: "Z" = (1/16" OR .0625 RAISED FACE ON EACH FLANGE)  
 NOTE 9: RATED AND TESTED FOR 250 PSI WORKING PRESSURE  
 NOTE 10: APPROXIMATE WEIGHT = 6300LBS

PROJECT

OWNER

CONTRACTOR

DISTRIBUTOR

CONSULTANT

**CLOW CANADA**

1200mm STYLE 1450  
 CLASS 250 BUTTERFLY VALVE  
 NON-INDICATING FLG x FLG

DWG. No.  
 BFE-25-48A