



	OPERATOR MODEL	D	E	F	H	K	L	M	N
750	2200	230	159	264	268	273	98	152	72
900 & 1050	4350	255	154	384	457	338	106	190	90

VALVE SIZE	A	B	C	J	P	Q	R	R1	S	AA	AB	WEIGHT lbs
750mm	577	600	997	349	28	44.45	1092	944	76	4	1 3/4-5	1850
900mm	664	687	1168	355	32	50	1270	1109	86	4	2-4 1/2	2600
1050mm	762	786	1340	360	36	50	1448	1280	94	4	2-4 1/2	4500

- NOTE 1: FLOW MAY BE IN EITHER DIRECTION  
 NOTE 2: VALVE SHAFT WILL MEET OR EXCEED REQUIREMENTS OF SHAFT TABLE PER AWWA STANDARD C-504 FOR APPLICABLE CLASS.  
 NOTE 3: REFERENCE AWWA C-504 FLANGES & DRILLING (A.N.S.I. 250)  
 NOTE 4: "N" = NUMBER OF TURNS TO CLOSE  
 NOTE 5: "P" = NUMBER OF BOLTS ON EACH FLANGE  
 NOTE 6: "Q" = DIAMETER OF BOLTS  
 NOTE 7: OPERATED BY 50mm AWWA OPERATING / WRENCH NUT  
 NOTE 8: RATED AND TESTED FOR 250 PSI WORKING PRESSURE  
 NOTE 9: "Z" = (1.59mm RAISED FACE ON EACH FLANGE)

PROJECT

OWNER

CONTRACTOR

DISTRIBUTOR

CONSULTANT

**CLOW CANADA**

750mm - 1050mm STYLE 1450  
 CLASS 250 BUTTEFLY VALVE  
 INDICATING FLG x FLG

DWG. No.  
 A-8028