

**RESILIENT WEDGE VALVES SHIPPING WEIGHTS**

**ALL WEIGHTS IN POUNDS**

|      | F6100                          | F6106                        | F6112                            | F6113                             |
|------|--------------------------------|------------------------------|----------------------------------|-----------------------------------|
| SIZE | MJ x MJ<br><i>less MJ acc.</i> | FLG x MJ<br><i>less acc.</i> | PO x PO<br><i>with po gasket</i> | FLG x PO<br><i>with po gasket</i> |
| 4"   | 87                             | 86                           | 87                               | 88                                |
| 6"   | 136                            | 140                          | 135                              | 138                               |
| 8"   | 206                            | 210                          | 211                              | 214                               |
| 10"  | 352                            | 358                          | 355                              | 360                               |
| 12"  | 480                            | 436                          | 496                              | 505                               |
| 14"  | 625                            | 750                          | 605                              | N/A                               |
| 16"  | 675                            | 850                          | 700                              | N/A                               |

ALL 18" DIAMETER + VALVES ARE EQUIPT WITH EITHER A BEVEL (HORIZONTAL INSTALLATION) OR SPUR (VERTICAL INSTALLATION) GEAR OPERATOR

|     |       |       |     |     |
|-----|-------|-------|-----|-----|
| 18" | 1,325 | 1,400 | N/A | N/A |
| 20" | 1,325 | 1,500 | N/A | N/A |
| 24" | 1,970 | 1,800 | N/A | N/A |
| 30" | 5,330 | 5,400 | N/A | N/A |
| 36" | 6,330 | TBA   | N/A | N/A |

|      | F6114                           | F6115                             | F6111                          |
|------|---------------------------------|-----------------------------------|--------------------------------|
| SIZE | MJ x TAP<br><i>less MJ acc.</i> | PO x TAP<br><i>with po gasket</i> | CUTTING IN<br><i>less acc.</i> |
| 4"   | 89                              | 88                                | 71                             |
| 6"   | 142                             | 138                               | 114                            |
| 8"   | 214                             | 214                               | 178                            |
| 10"  | 378                             | 360                               | 312                            |
| 12"  | 523                             | 505                               | 438                            |

|        | F6102             | F6102H            | F6110                | F6103        | F 8068 OS&Y       |
|--------|-------------------|-------------------|----------------------|--------------|-------------------|
| SIZE   | Flanged 2" OP Nut | Flanged Handwheel | PO x PO PVC IPS size | Threaded FIP | Flanged Handwheel |
| 2"     | 39                | 43                | 37                   | 33           | 39                |
| 2 1/2" | 51                | 56                | 47                   | 44           | 55                |
| 3"     | 62                | 68                | 57                   | 50           | 67                |
| 4"     | 87                | 93                | 85                   | N/A          | 87                |
| 6"     | 134               | 143               | 220                  | N/A          | 138               |
| 8"     | 212               | 224               | 220                  | N/A          | 214               |
| 10"    | 369               | 388               | N/A                  | N/A          | 360               |
| 12"    | 523               | 542               | N/A                  | N/A          | 505               |
| 14"    | 665               | 690               | N/A                  | N/A          | TBA               |
| 16"    | 720               | 745               | N/A                  | N/A          | TBA               |

ALL 18" DIAMETER + VALVES ARE EQUIPT WITH EITHER A BEVEL (HORIZONTAL INSTALLATION) OR SPUR (VERTICAL INSTALLATION) GEAR OPERATOR

|     |       |       |     |     |     |
|-----|-------|-------|-----|-----|-----|
| 18" | 1,425 | 1,450 | N/A | N/A | TBA |
| 20" | 1,350 | 1,375 | N/A | N/A | TBA |
| 24" | 1,940 | 1,965 | N/A | N/A | TBA |
| 30" | 5,275 | 5,300 | N/A | N/A | TBA |
| 36" | 7,220 | 7,245 | N/A | N/A | TBA |

ALL 14" DIAMETER + VALVES ARE REDUCED WALL THICKNESS DUCTILE IRON & MEET OR EXCEED THE REQUIREMENTS OF AWWA C515

N/A- Not Available

**FIRE HYDRANT SHIPPING WEIGHTS**

CLOW McAVITY CONCORD BIBBY

| TRENCH | DEPTH | 2 HOSE W/PUMPER | 2 HOSE W/STORZ |
|--------|-------|-----------------|----------------|
| 1.07M  | 3'6"  | 430             | 430            |
| 1.22M  | 4'0"  | 450             | 450            |
| 1.37M  | 4'6"  | 470             | 470            |
| 1.52M  | 5'0"  | 490             | 490            |
| 1.68M  | 5'6"  | 510             | 510            |
| 1.83M  | 6'0"  | 530             | 530            |
| 1.98M  | 6'6"  | 550             | 550            |
| 2.13M  | 7'0"  | 570             | 570            |
| 2.29M  | 7'6"  | 590             | 590            |
| 2.43M  | 8'0"  | 610             | 610            |
| 2.59M  | 8'6"  | 640             | 640            |
| 2.74M  | 9'0"  | 680             | 680            |
| 2.90M  | 9'6"  | 700             | 700            |
| 3.10M  | 10'0" | 720             | 720            |